EASYPLISE POC-3





Reliability and Purity In the Smallest Package

Proven Reliability

Precision Medical's Portable Oxygen Concentrators have the lowest return rate and repair rate on the market. Our POC's have proven to be incredibly durable even under the stress and rigors of everyday use.

Highest Purity

Our EasyPulse POC has been a proven leader in oxygen purity delivered to the patient. The EasyPulse POC-3 is no exception.

The highest oxygen purity, coupled with a 3 year warranty on the sieve beds, allow peace of mind for both provider and patient.

Reliable Delivery

Precision Medical incorporates CMV technology used in the EasyPulse5 Oxygen Conserver, the largest selling O2 conserver on the market. CMV technology delivers therapeutic oxygen to the patient in the first 1/3 of the inspiratory phase for maximum efficiency.

Easier to Use

Simply turning the knob or pushing a button easily sets the oxygen flow. No confusing electronic controls to operate the unit.

Proven Battery Life

The EasyPulse POC-3 has a battery duration up to 11 hours. This allows the patient to be mobile with the confidence that their oxygen needs will be met, at home as well as when traveling. Precision Medical's patented Control Minute Volume (CMV) technology insures battery duration stays consistent on all flow settings.

Smallest and Lightest

With a footprint of only 8.5" height x 4.5 " length x 6.5" width. The EasyPulse POC-3 is the smallest unit on the market. All the features above are provided in a POC weighing 4.9 lbs.





EasyPulse POC shown in Carry Bag

External Battery PN 506760

Handle

Power Input Jack

Setting Knob

Exhaust Vents

Setting 1:

Setting 2:

Setting 3: Sound (@ Setting 2): 42 dBA Cannula:

nasal cannula

Power:

Breath Rate Range:

AC Power Adaptor:

DC Power Adaptor:

3 years on device

180 days on internal battery 180 days on external battery Specifications are subject to change without prior notice.

Setting 1:

Setting 2:

Setting 3:

Warranty:

up to 35 Breaths per Minute

Battery Duration at any breath rate (approx.):

5.5 hrs

3.8 hrs

2.8 hrs

Oxygen Minute Volume (at sea level):

SPECIFICATIONS

Dimensions:

Dimonorono	
Without Bag:	Height 8.5 in. (21.6 cm),
0	Length 4.5 in. (11.4 cm)
	Width 6.5 in (16.5 cm),
In Bag:	Height 9.0 in. (22.9 cm),
-	Length 5.0 in. (12.7 cm)
	Width 10.0 in (25.4 cm),
Weight:	
Without Bag:	4.9 lbs (2.22 kg)
In Bag:	5.4 lbs (2.45 kg)

Shipping: 10.8 lbs (4.91 kg)

- **Operating Temperature Range:** 41°F to 104°F (5°C to 40°C) Altitude: Sea Level to 14000 ft (4267 m)
- Storage Temperature:
- -4°F to 140°F (-20°C to 60°C)
- **Relative Humidity:**
- Up to 95% Non-condensing

Oxygen Concentration: 87% to 95%

ORDERING INFORMATION

Part Number	Description
PM4130	EasyPulse POC-3 Oxygen Concentrator (dial model) - includes AC and DC Power Supplies, Cords, Carry Bag & Cannula
PM4130EB	EasyPulse POC-3 Oxygen Concentrator (dial model) - includes AC and DC Power Supplies, Cords, Carry Bag, Cannula & External Battery
PM4130P	EasyPulse POC-3 Oxygen Concentrator (push button model) - includes AC and DC Power Supplies, Cords,
	Carry Bag & Cannula
PM4130PEB	EasyPulse POC-3 Oxygen Concentrator (push button model) - includes AC and DC Power Supplies, Cords, Carry Bag, Cannula & External Battery

Part Number	Description
504833	Cannula
505847	Filter
506629	AC Power Supply
506750	DC Power Supply
506760	External Battery
506961	AC Power Cord
507947	Carry Bag

Precision Medical. Inc. 300 Held Drive • Northampton, PA 18067 USA Toll-Free Phone: 1-800-272-7285 Phone: (+001) 610-262-6090 (+001) 610-262-6080 Fax:



Inlet Filter

Internal Battery Level Indicator

Oxygen Outlet Fitting

Alarm Indicator

-

123

PM4130P **Push Button**

Setting Panel

240 ±15% ml/min

380 ±15% ml/min

520 ±15% ml/min

Maximum 7 ft (2.1 m) long standard adult single lumen

100-240 VAC (1.0 A @ 120 VAC)

11-16 VDC (5.0 A @ 12 VDC)